

AUPLUS A/T M/T TIRES

AUPLUS brand owned by Poplar Tire Co., Ltd, is best known for its commitment to meeting customer demand of safety, comfort, affordability & high performance. A/T, M/T tires are designed and developed especially for light trucks and SUVs in All-terrain and mud/rough using conditions. All series are built and developed in renowned tire manufacturers.

- 
- ★ Designed for all terrain using condition considered high speed stability.
 - ★ Big foot design ensures more friction force with rough roads to avoid skid.
 - ★ Strengthened and thickened sidewalls to protect pebbles stones attack.
 - ★ M/T directional design easily exhaust mud and stones.
 - ★ Certificates: ISO9001:2008, GCC, SONCAP, DOT, E-MARK, S-MARK, INMETRO.
 - ★ Product Liability Insurance
 - ★ Optimum price-performance ratio, affordability.
 - ★ Marketing team support.

QINGDAO POPLAR TIRE CO.,LTD

ADD: 10th Floor, International Development Center, No. 36 Miaoling Road, Qingdao, China
Tel: 86 532 68721277 (68721527 68721529 68721551 68721552 68721587 68721603)
Fax: 86 532 68721528 E-mail: info@poplartire.com

www.poplartire.com www.auplustire.com

AUPLUS

PASSENGER CAR TYRE BROCHURE

PLUS AT / PLUS MT



- All terrain use condition
- High speed stability ensured
- Strengthened sidewall protection
- Minimized noise level

PLUS AT

INCH	SIZES	PR	LI & SR	SIDEWALL	RIM	S.W.(mm)	O.D(mm)
15	P215/75R15	-	102S/100S	OWL	6.0	216	703
	P235/75R15	-	108S	OWL	6.5	235	733
	P215/70R16	-	99T	OWL	6.5	221	708
16	P235/70R16	-	104T	OWL	7.0	240	736
	P245/70R16	-	106S	OWL	7.0	248	750
	P265/70R16	-	111T	OWL	8.0	272	778
17	P265/65R17	-	110T	OWL	8.0	272	776
16	LT235/85R16	10	120/116S	OWL	6.5	235	806
	LT245/75R16	10	120/116S	OWL	7.0	248	774
	LT265/75R16	10	123/120S	OWL	7.5	267	804
17	LT265/70R17	10	121/118S	OWL	8.0	272	804
16	265/70R16 LT	10	121/118S	OWL	8.0	272	778
17	285/70R17LT	10	121/118S	OWL	8.5	292	832
16	285/75R16LT	10	126/123S	OWL	8.0	286	834
15	30×9.50R15LT	6	104R	OWL	6.0	240	750
	31×10.50R15LT	6	109S	OWL	6.0	268	775
17	35×12.50R17LT	10	121S	OWL	10.0	318	877
18	35×12.50R18LT	10	123S	OWL	10.0	318	877
20	35×12.50R20LT	10	121S	OWL	10.0	318	877



- Directional design, easy self-cleaning
- Maximum traction
- Thickened sidewall

PLUS MT

INCH	SIZES	PR	LI & SR	SIDEWALL	RIM	S.W.(mm)	O.D(mm)
15	LT215/75R15	6	100/97Q	OWL	6.0	216	709
	LT235/75R15	6	104/101Q	OWL	6.5	235	739
	LT215/85R16	10	115/112Q	-	6.0	216	778
16	LT235/85R16	10	120/116Q	-	6.5	235	812
	LT225/75R16	10	115/112Q	-	6.0	223	750
	LT245/75R16	10	120/116Q	-	7.0	248	780
	LT265/75R16	10	123/120Q	OWL	7.5	267	810
	LT285/75R16	10	126/123Q	OWL	8.0	286	840
	LT315/75R16	10	127/124Q	OWL	8.5	313	884
	LT305/70R16	8	118/115Q	OWL	9.0	311	840
17	LT265/70R17	10	121/118Q	-	8.0	272	810
	LT285/70R17	8	121/118Q	-	8.5	292	838
15	31×10.50R15LT	6	109Q	OWL	8.5	268	781
	32×11.50R15LT	6	113Q	OWL	9.0	290	807
	33×12.50R15LT	6	108Q	OWL	10.0	318	832
17	33×12.50R17LT	6	114Q	OWL	10.0	318	832
	35X12.50R17LT	10	121Q	OWL	10.0	318	883
18	33×12.50R18LT	10	118Q	OWL	10.0	318	832
	35X12.50R18LT	10	123Q	OWL	10.0	318	883
20	33×12.50R20LT	10	114Q	OWL	10.0	318	832
	35×12.50R20LT	10	121Q	OWL	10.0	318	883
	35×13.50R20LT	10	124Q	OWL	10.0	345	883

AUPLUS A/T M/T TIRES